




Vlastnosti



- Proiectat special pentru a putea fi instalat la orice fel de u?? rotativ?. Dou? aspecte posibile, dimensiuni personalizate.
- Carcas? autoportant? f?cut? din plac? de o?el galvanizat, finisat? standard cu o vopsea structurat? RAL9016, de culoare alb?, din epoxi-poliester.Alte culori sau o?el inoxidabil, disponibile la cerere.
- Grilaj de admisie larg, fa?et?at, f?r? mentenan?? intensiv?.
- Palete de evacuare circulare din aluminiu anodizat, cu form? aerodinamic?.
- Ventilatoare centrifugale cu dubl? admisie, alimentate de motor extern cu rotor ?i cu zgomot redus. Selector de 5 viteze.Modele EC asamblate cu ventilatoare eficiente cu consum redus.
- Tip "P", pentru bobin? de încălzire pe ap?.Tip "E" cu componente protejate electric, trei stadii cu ajustare integrat?.Tip "A" f?r? încălzire, doar aer.Bobin? de expansiune DX op?ional?.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 10m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
 - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
 - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.

Specifikace

50Hz

Neohřívání				
Model	(m³/h)	(m)		
ROTO BB 1000 A	5-7			
ROTO BB 1500 A	5-7			
ROTO BB 2000 A	5-7			
ROTO BB 2500 A	5-7			
ROTO SB 1000 A	3,5-5			
ROTO SB 1500 A	3,5-5			
ROTO SB 2000 A	3,5-5			
ROTO SB 2500 A	3,5-5			

Elektrický ohřev				
Model	(m³/h)	(kW)	(m)	(kW)
ROTO BB 1000 E	-			
ROTO BB 1500 E	-			
ROTO BB 2000 E	-			
ROTO BB 2500 E	-			
ROTO SB 1000 E	12,44			
ROTO SB 1500 E	-			
ROTO SB 2000 E	-			
ROTO SB 2500 E	-			

Ohřev vodou				
Model	(m³/h)	(m)	(kW)	(kW)
ROTO BB 1000 P86	-			



Ohřev vodou					
Model	(m³/h)	(m)	(kW)	(kW)	(kW)
ROTO BB 1500 P86	-				
ROTO BB 2000 P86	-				
ROTO BB 2500 P86	-				
ROTO SB 1000 P86	-				
ROTO SB 1500 P86	-				
ROTO SB 2000 P86	-				
ROTO SB 2500 P86	-				
ROTO BB 1000 P64	-				
ROTO BB 1500 P64	-				
ROTO BB 2000 P64	-				
ROTO BB 2500 P64	-				
ROTO SB 1000 P64	-				
ROTO SB 1500 P64	-				
ROTO SB 2000 P64	-				
ROTO SB 2500 P64	-				
ROTO BB 1000 P54	36,57				
ROTO BB 1500 P54	15,16				
ROTO BB 2000 P54	38,96				
ROTO BB 2500 P54	24,15				
ROTO SB 1000 P54	14,47				
ROTO SB 1500 P54	21,19				
ROTO SB 2000 P54	30,77				
ROTO SB 2500 P54	36,94				

60Hz

Neohříváná		
Model	(m³/h)	(m)
ROTO BB 1000 A	5-7	
ROTO BB 1500 A	5-7	
ROTO BB 2000 A	5-7	
ROTO BB 2500 A	5-7	

Elektrický ohřev				
Model	(m³/h)	(kW)	(m)	(kW)
ROTO BB 1000 E	-			
ROTO BB 1500 E	-			
ROTO BB 2000 E	-			
ROTO BB 2500 E	-			

Ohřev vodou					
Model	(m³/h)	(m)	(kW)	(kW)	(kW)
ROTO BB 1000 P86	-				
ROTO BB 1500 P86	-				
ROTO BB 2000 P86	-				
ROTO BB 2500 P86	-				
ROTO BB 1000 P64	-				



Ohřev vodou					
Model	(m³/h)	(m)	(kW)	(kW)	(kW)
ROTO BB 1500 P64	-				
ROTO BB 2000 P64	-				
ROTO BB 2500 P64	-				
ROTO BB 1000 P54	36.57				
ROTO BB 1500 P54	15.16				
ROTO BB 2000 P54	38.96				
ROTO BB 2500 P54	24.15				

Rozměry

