




Vlastnosti



- Specially designed to be installed on doors of industrial cold stores and freezers with big temperature differences.
- The Twin Kool air curtain system has been designed to offer a versatile solution for any type of cold room. It has two jets of opposing air chambers that create additional space between the chamber and the pre-chamber. Thanks to the double barrier, this model becomes the perfect alternative to the TRIOJET SYSTEM air curtain when space is limited or this model is not an option.
- Carcas? autoportant? f?cut? din plac? de o?el galvanizat, finisat? standard cu o vopsea structurat? RAL9016, de culoare alb?, din epoxi-poliester. Alte culori sau o?el inoxidabil, disponibile la cerere.
- Grilaj de admisie larg, fa?etat, f?r? mentenan?? intensiv?.
- Palete de evacuare din aluminiu anodizat, cu form? aerodinamic?, ajustabil? pe fiecare parte de la 0 la 15?.
- Ventilatoare centrifugale cu dubl? admisie, alimentate de motor extern cu rotor ?i cu zgomot redus. Selector de 5 viteze. Modele EC asamblate cu ventilatoare eficiente cu consum redus.
- Tip "A" f?r? ?nc?lzire, doar aer.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
 - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
 - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.
- Includes varnishing on the PCB to protect it from corrosion.

Specifikace

50Hz

Neoh?ívaná		
Model	(m²/h)	(m)
TWIN KECG 3000 A	9,8-13,8	
TWIN KM 1500 A	9,8-13,1	
TWIN KM 2000 A	9,8-13,1	
TWIN KM 2500 A	9,8-13,1	
TWIN KM 3000 A	9,8-13,1	
TWIN KECM 1500 A	9,8-13,8	
TWIN KECM 2000 A	9,8-13,8	
TWIN KECM 2500 A	9,8-13,8	
TWIN KECM 3000 A	9,8-13,8	
TWIN KG 1500 A	9,8-13,1	
TWIN KG 2000 A	9,8-13,1	
TWIN KG 2500 A	9,8-13,1	
TWIN KG 3000 A	9,8-13,1	
TWIN KECG 1500 A	9,8-13,8	
TWIN KECG 2000 A	9,8-13,8	
TWIN KECG 2500 A	9,8-13,8	

60Hz

Neoh?ívaná



Model	(m³/h)	(m)
TWIN KECM 1500 A	9,8-13,8	
TWIN KECM 2000 A	9,8-13,8	
TWIN KECM 2500 A	9,8-13,8	
TWIN KECM 3000 A	9,8-13,8	

Rozm?ry

